

MX150 Sealed Connector System

The field-proven MX150 Sealed Connector System with a USCAR interface offers a compact package, a superior operating temperature and a current rating up to 22.0A for power and signal automotive and commercial vehicle applications.

FEATURES AND ADVANTAGES: Sealed Single- and Dual-Row Connector System

Mat seal technology for MX150 (1.50mm) Terminals

Eliminates the need for individual cable seals which provides reduced package size and reduced cost

Connector position assurance (CPA) option available

Assures connectors have been fully mated and prevents accidental disconnection

Temperature class (-40 to +150°C) and 22.0A current rating

Delivers superior performance

1-piece 3.5mm-pitch housing

Eliminates unnecessary and costly assembly operations. Offers a compact connector

Preassembled terminal position assurance (TPA) housing

Ensures crimped terminal leads are properly locked into connector

Single- and dual-row V0 versions available (UL1977 certified)

Meets stringent safety requirements

Conforms to USCAR-2/USCAR-21/GMW3191

For use in on-engine, high-vibration, under-hood and under-chassis environments at temp class 4

Grommet cap

Protects the mat seal and assures proper alignment of the terminals

USCAR Interface

Released & approved interface for major North America OEMs

4 polarization and color options

Facilitates quick visual installation

Single- and dual-row backshells/wire dress covers available in 2-, 3-, 6-, 8-, 12-, 16- and 20-circuit sizes

Provides additional protection of the wires out the back of the connector. Secures cable bundle. Provides strain relief

Flashover options

(custom void patterns) available

Provides design flexibility



Twist-Head Sealed Bulkhead Connectors

Clip-slot feature standard on blade connectors, optional on receptacle

Fastens/attaches clips. USCAR standard 11.00mm clip slot

2x3 and 2x6 Panel-Mount Now Available; 20-Way V0 Version Coming in Q2 2021

Flashover options (i.e., custom void patterns) available

Provides design flexibility

FEATURES AND ADVANTAGES: Hybrid Connector

10-way hybrid receptacles 12- and 16-way hybrid receptacle and blade connectors

8-way hybrid receptacles

9-way receptacles 8-, 9- and 10-way blade connectors

Offers versatility to meet a range of applications

Mat seal technology for MX150 (1.50mm) Terminals

Eliminates the need for individual cable seals which provides reduced package size and reduced cost

Grommet Cap


Protects the mat seal and assures proper alignment of the terminals

Pre-assembled terminal position assurance (TPA) housing

Ensures crimped terminal leads are properly locked into connector

11.00mm clip slot standard on blade connector and optional on receptacle

Fastens/attaches clips




MX150 Sealed Connector System >

FEATURES AND ADVANTAGES: Hybrid Connector (Continued)

Backshells/wire dress covers available
Secures cable. Provides strain relief

*Hybrid 8-way Receptacle:
Six 1.50mm Circuits and
Two 6.30mm Circuits*



Connector position assurance (CPA) option available
Assures connectors have been fully mated and prevents accidental disconnection

Meets GMW3191 and USCAR-2 specifications
Ensures reliable performance.
Mates with USCAR interfaces

4 key options available
Facilitates quick visual installation



*Hybrid 12-Way Connector System,
Blade and Receptacle:
Ten 1.50mm Circuits and
Two 2.80mm Circuits*

FEATURES AND ADVANTAGES: Terminals

Tin, Silver and Gold options available for blade and receptacle matte seal and cable seal terminals
Offers reliable, economic connectivity

**Tin rated up to temp class 3 (-40 to +125°C)
Silver rated up to temp class 4 (-40 to +150°C)**
Delivers superior performance

Current rating up to 22.0A
Delivers superior performance

Validated: USCAR-21, USCAR-2 and GMW3191 specs
Meets industry standards

Validated wires to GM, Ford, PSA and JASO specifications
Meets requirements of major auto manufacturers



MARKETS AND APPLICATIONS

Automotive and Commercial Vehicle

- Transmissions
- Head/tail lamps
- Body harnesses
- Wipers, washers, defoggers
- Speedometers
- A/C modules
- Turn signals
- Airbag harnesses
- Speakers
- Door connectors
- Brake modules
- Horns

Wipers, washers, defoggers

Speedometer

A/C Module


Turn Signals

Airbag Harness

Speakers

Seat Harness

Horn



MX150 Sealed Connector System >

SPECIFICATIONS

SEALED CONNECTORS AND RECEPTACLES

REFERENCE INFORMATION

Packaging:
Housings – Bulk pack
Terminals – Reel
Mates With:
Receptacle Connectors, Series 33471, 33472, 34985
Blade Connectors, Series 33481, 33482, 34986
Use With:
- Terminals:
Receptacles, Series 33001, 33012
Blades, Series 33000, 33011
Backshells, Series 34948, 34949, 34950, 34951
Cavity Plugs, Order No. 34345-0001
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 500V
Current (max.): 22.0A
Contact Resistance: 10 milliohms max.
Dielectric Withstanding Voltage: 1500V AC min.
Isolation Resistance: 20 Megohms min.

MECHANICAL/ELECTRICAL/SEALING

Mating Force: Less than 75N max.
Unmating Force: Less than 75N max.
Connector Retention (Primary Latch): 255N (57.33 lb) avg.
(exceeds 110N [24.73 lb] min. USCAR requirement)
Contact Retention to Housing: 210N (47.21 lb) avg.
(exceeds 90N (20.23 lb) min. USCAR requirement)
Contact Insertion Force Into Housing: 30N (6.74 lb) max.
Contact Insertion Force: 4.4N (1.0 lb) max.
Connector Audible Feedback: 7dB over ambient
Polarization Feature Effectiveness: 220N (49.46 lb) min.
FCLT (Class 3): 20 milliohms max.
Durability: 10 milliohms max.
Tin (Sn) Plating – 25 Cycles
Silver (Ag) Plating – 100 Cycles
Gold (Au) Plating – 100 Cycles
Thermal Shock (class 3, 100 cycles): 10 milliohms max.
High-Temperature Exposure:
Pressure/Vacuum Immersion – 28 kPa (4psi) 30 minutes
Isolation Resistance – 20 Megohms @ 500V DC min.
Vibration: (USCAR-2 Rev 4) 10 milliohms max.
Random “On-Engine” Profile: 118.7 mps² rms, 60 to 1,200 Hz
Mechanical Shock: 343 mps², half-sine wave, 10 msec Pulse
Vibration: (GMW 3191) 10 milliohms max.

Random “On-Engine” Profile: 170 mps² rms, 10 to 1,500Hz
Sine “On-Engine” Profile: 280 mps² Pk, 100-440 Hz
Mechanical Shock: 245 mps², half-sine wave, 10 msec pulse
Sealing: (USCAR-2 Rev 4) (GMW3191)
Heat Soak Submersion: +125°C and submersion depth of 40.00cm (15.75”) water
Pressure/Vacuum Immersion: 48 kPa (7 psi) IEC 529, IPX9K when used with CPA, Backshell and Conduit
Isolation Resistance: 20 Megohms @ 500V DC min.

PHYSICAL

Housing: SPS/Nylon Blend 20%GF, UL 94-HB
TPA: SPS/Nylon Blend 20%GF
Contact: Copper (Cu) Alloy
Plating:
Contact Area — Tin (Sn), Gold (Au) or Silver (Ag)
Underplating — Nickel (Ni)
Wire Gauge:
ISO Wire: 0.35 to 1.50mm² SAE Wire: 22AWG to 14AWG
Insulation Diameter: 2.70 to 1.50mm
Operating Temperature: -40 to +125°C (Sn), -40 to +150°C (Ag)

SEALED HEADERS

REFERENCE INFORMATION

Packaging:
Headers – Trays
Mates With:
Receptacle connectors, Series 33472
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 500V DC
Current (max.): 22.0A
Contact Resistance (max.): 10 milliohms
Dielectric Withstanding Voltage: 1000V
Isolation Resistance (min.): 20 Megohms min.

MECHANICAL/ELECTRICAL/SEALING

Durability (max.): 10 milliohms at 10 cycles
Sealing: IP6k9k w Backshells

PHYSICAL

Housing: PBT 30% Glass Filled
Terminal: Copper (Cu) Alloy
Size: 1.20 X 0.80 mm
Plating: Tin (Sn) (Silver (Ag) coming soon)
Underplating: Nickel (Ni)
PCB Interface: Solder tail or Compliant pin
Module attachment type: Adhesive
Operating Temperature: -40 to +125°C

PANEL-MOUNT CONNECTORS

REFERENCE INFORMATION

Packaging:
Housings – Packed in trays
2x6 Series: 47725
2x3 Series: 148028
Mates With:
Receptacle Connectors, Series 33472
Use With: Blade Terminals, Series 33000, 33011
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 500V DC
Current (max.): 22.0A
Contact Resistance: 8 milliohms max.
Dielectric Withstanding Voltage: 1000V AC min.
Isolation Resistance: 100 Megohms min.

MECHANICAL/ELECTRICAL/SEALING

Durability: 8 milliohms max. at 10 cycles
Sealing: GMW3191 Sealing Class 2 & IP6k9k with Backshells

PHYSICAL

Housing: SPS/Nylon 20% Glass Filled, UL 94-HB
TPA: 20% Glass Filled SPS/Nylon
Wire Gauge: ISO Wire: 0.35 to 1.50mm² SAE Wire: 22 to 14 AWG
Insulation Diameter: 2.69 to 1.20mm (.106 to .047”)
Operating Temperature: -40 to +125°C

MX150 Sealed Connector System

SPECIFICATIONS

TWIST-LOCK SEALED BULKHEAD CONNECTORS

REFERENCE INFORMATION

Packaging:
Housings – Packed in trays
Mates With:
Receptacle Connectors, Series 33472
Use With: Blade Terminals, Series 33000
and 33011
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 14V DC
Current (max.): 22.0A
Contact Resistance (max.): 8 milliohms
Dielectric Withstanding Voltage: 1000V
Isolation Resistance (min.): 100 Megohms min.

MECHANICAL/ELECTRICAL/SEALING

Durability: 8 milliohms max. at 10 cycles
Sealing: GMW3191 Class 2

PHYSICAL

Housing: SPS/Nylon 20% GF, UL 94-HB
TPA: 20% Glass-Filled SPS/Nylon
Wire Gauge: ISO Wire: 0.35 to 1.50mm², SAE Wire:
22 to 14 AWG
Operating Temperature: -40 to +105°C

STANDARD AND M3 GRIP TERMINALS

REFERENCE INFORMATION

Packaging: Reel (terminals are not packaged
with connectors)
Use With:
Receptacle Connector Series 33471, 33472, 34985
Blade Connector Series 33481, 33482, 34986
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 500V
Current (max.): 12.5A

PHYSICAL

Contact: Copper (Cu) Alloy
Plating:
Contact Area — Tin (Sn), Silver (Ag), Gold (Au)
Underplating — Nickel (Ni)
Wire Gauge:
ISO Wire: 0.35 to 2.00mm²
SAE Wire: 22 to 14 AWG
Operating Temperature: -40 to +125°C – Tin (Sn)
Operating Temperature: -40 to +155°C – Silver (Ag)

12W HYBRID CONNECTORS (SERIES 160111, 160112)

REFERENCE INFORMATION

Packaging:
Housings – Bulk Pack
Mates With:
Receptacle Connectors, Series 160111
Blade Connectors, Series 160112
Use With:
MX150 Receptacle Terminals, Series 33012, 33001
MX150 Blade Terminals, Series 33000, 33011
Sumitomo Receptacle Terminal Part Numbers,
8240-0423, 8240-0424
Sumitomo Blade Terminal PN's, 8230-5257,
8230-5258
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 500V DC
Current (max.): 22.0A (For MX150 Terminals)
Contact Resistance: 8 milliohms max.
Dielectric Withstanding Voltage: 1000V AC min.
Isolation Resistance: 100 Megohms min.

MECHANICAL/ELECTRICAL/SEALING

Durability: 8 milliohms max. at 10 cycles
Sealing: USCAR-2 Sealing Class 2

PHYSICAL

Housing: Nylon 40% Glass Filled
TPA: Nylon 40% Glass Filled
Wire Gauge:
MX150 Terminals ISO Wire: 0.35 to 1.50mm², SAE
Wire: 22 to 14 AWG
Sumitomo 2.80mm Terminals: 1.00 to 2.50mm²
Insulation Diameter: 2.69 to 1.20mm
(.106 to .047")
Operating Temperature: -40 to +125°C

10W HYBRID RECEPTACLE CONNECTORS (SERIES 160076)

REFERENCE INFORMATION

Packaging:
Housings – Bulk Pack
Use With:
μDPB Modules (series 200316); MX150 Receptacle
Terminals, Series 16077 (coming January 2021)
Apex 6.30mm Receptacle Terminal PN: 33140138
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 500V DC
Current (max.): 22.0A (For MX150 Terminals)
Contact Resistance: 8 milliohms max.
Dielectric Withstanding Voltage: 1000V AC min.
Isolation Resistance: 100 Megohms min.

MECHANICAL/ELECTRICAL/SEALING

Durability: 8 milliohms max. at 10 cycles
Sealing: USCAR-2 Sealing Class 2

PHYSICAL

Housing: Nylon 40% Glass Filled
TPA: Nylon 40% Glass Filled
Wire Gauge:
MX150 Terminals ISO Wire: 0.35 to 1.50mm², SAE
Wire: 22 to 14 AWG
Unsealed FCI Apex 2.80mm Terminals:
1.00 to 3.00mm²
Operating Temperature: -40 to +125°C

MX150 Sealed Connector System

SPECIFICATIONS

8W HYBRID RECEPTACLE CONNECTORS (SERIES 160078)

REFERENCE INFORMATION

Packaging:
Housings – Bulk Pack
Use With:
μDPB Modules (series 200316);
MX150 Receptacle Terminals, Series 33012, 33001
Apex 6.3mm Receptacle Terminal PN: 33140138
Designed in: Millimeters

ELECTRICAL

Voltage (max.): 500V DC
Current (max.): 22.0A (For MX150 Terminals)
Contact Resistance: 8 milliohms max.
Dielectric Withstanding Voltage: 1000V AC min.
Isolation Resistance: 100 Megohms min.

MECHANICAL/ELECTRICAL/SEALING

Durability: 8 milliohms max. at 10 cycles
Sealing: USCAR-2 Sealing Class 2

PHYSICAL

Housing: Nylon 40% Glass Filled
TPA: Nylon 40% Glass Filled
Wire Gauge:
MX150 Terminals ISO Wire: 0.35 to 1.50mm²,
SAE Wire: 22 to 14 AWG
Unsealed FCI Apex 6.30mm Terminals: 6.00mm²
Operating Temperature: -40 to +125 °C

www.molex.com/link/mx150.html